

	BW	ASB-Nr	Fläche [m2]	ÜKO	Material:					AC 32 TS (mind. 8 cm)	SMA 16 BS (6 - 9,5 cm)		SMA 8 LA
					Annahme Bestandsdicke (inkl. DSK)	Annahme Bestandsdicke (ohne DSK)	Annahme Bestandsmaterial	Höhenunter- schied Farbhan neu/ alt	neue Aufbaustärke	ATS Ausgleich	ABS Ausgleich	ABS konstant	ADS
Nordabschnitt	BW00	4807 500	665	x	15,000	14,500	???	0,000	15,000		3,000	9,000	3,000
	BW03	4807 506	698,2		13,025	12,525	Asphalt	1,000	14,025		11,025		3,000
			232,7			3,900	GA						
			232,7			3,300	ABS						
			232,7			6,300	ATS						
			465,5			12,450	Beton (bewehrt)						
	BW05	4807 509	408,6		17,280	16,780	Asphalt	1,000	18,280		6,280	9,000	3,000
			136,2			2,400	GA						
			136,2			7,600	ABS						
			136,2			6,000	ATS						
			272,4			17,150	Beton (bewehrt)						
BW08	4807 512	69,6		26,130	25,630	Beton (bewehrt)	4,000	30,130	18,130		9,000	3,000	
BW09	4807 514	352,3		15,000	14,500	Beton (bewehrt)	-3,000	12,000		9,000		3,000	
BW10	4807 515	262,9		Überschüttet Rückbau und Neuaufbau wie durchgehende Strecke									
BW11	4807 516	269,5		17,100	16,600	Beton (bewehrt)	-4,000	13,100		10,100		3,000	
Südabschnitt	BW12	4807 519	1185	2x	11,300	10,800	Gussasphalt	2,000	13,300		10,300		3,000
	BW13	4807 521	256,5		14,950	14,450	Beton (bewehrt)	-3,000	11,950		8,950		3,000
	BW14	4807 522	1178	2x	15,650	15,150	Beton (bewehrt)	-3,000	12,650		9,650		3,000
	BW15	4807 523	253,7		15,000	14,500	Beton (bewehrt)	-4,000	11,000		8,000		3,000
	BW16	4807 524	241,6		16,925	16,425	Beton (bewehrt)	-2,000	14,925		11,925		3,000
	BW17	4807 525	504,5	1x	15,567	15,067	Beton (bewehrt)	-4,000	11,567		8,567		3,000
	BW18	4807 526	1040,2		14,000	13,500	Beton (bewehrt)	-2,000	12,000		9,000		3,000
	BW19	4807 527	81,9		15,000	14,500	Beton (bewehrt)	-2,000	13,000		10,000		3,000